



# PROTECTO EXTRICATION WRAP™ RESCUE TAPE

Patent Pending

Professional Protection for First Responders as well as Victims of Collisions from getting cut on sharp metal and glass edges

View The Instructional Video at [www.ExtricationWrap.com](http://www.ExtricationWrap.com)



Protects From Sharp Edges

Used by Team NAVRA -United States during a recent session in Germany in March 2010. The U.S. came in 2nd place. It is recommended by First Responders for Extrication Protection.

Protecto Extrication Wrap Rescue Tape is so economical and easy to use, every First Responder, Fire Fighter, EMS, Emergency Vehicle, Ambulance and Safety Vehicle should have a roll on board. It also works for Urban Search And Rescue applications.

Protecto Extrication Wrap Rescue Tape works in both extreme cold and hot temperatures. The in-service temperature is from 0° F to 120° F.

### Advantages Include:

- **Easy to Use, Peel-And-Stick Roll with Quick-Release Edge Tab**
- Protects first responders and victims from the results of disentanglement tactics and other sharp areas caused by the collision
- Thin, conformable facer allows user to cover irregular sharp areas
- Can be used to hold glass in place or used to hold broken glass together while removing it
- Can be used as sharps protection in Urban Search And Rescue applications (USAR)
- Adheres to most surfaces including Steel, Aluminum, Chrome, Glass, Paint, Vinyl & Plastic
- Economical. One roll lasts through many Extrications
- Pressure Sensitive Adhesive Technology adheres down to 0° F
- Roll size: 12" X 50'. Average total roof removal uses less than 7.5 lineal feet
- Tough Three Ply Film surface resists puncture and tearing
- Disposable, no need to discard expensive blankets and padding
- Universal Emergency Bright Yellow and Red colored Arrows on Wrap can be used as safety markers and warning signs



Holds Broken Glass Together for Easy Removal



Quick-Release Edge Tab

PHYSICAL PROPERTIES	VALUE	TEST METHOD
Puncture Resistance	2300 psi	ASTM D412
Tensile Strength	80 psi	ASTM D412
Cold Bend Pliability	-30° F	ASTM D1970
Thickness	25 mils	
Adhesion to Steel & Glass	Excellent	

### Instructions:

- Cut desired length from roll, peel off release liner and apply over sharp or glass surface. Bunching the material together at top of sharp surface may assist in protection.
- Most time 20" lengths are used to protect from sharp or jagged surfaces.
- 20" strips can be pre cut with a prepared edge by pulling 1" of release liner and folding adhesive back onto itself for quick protection.

AVAILABLE THROUGH

1-800-759-9727  
[www.ExtricationWrap.com](http://www.ExtricationWrap.com)

